



TECHNICAL DATA

APPROVED FOR



HiPRESS 2



HiPRESS 4



HiPRESS 4 duo



NOTE: All devices are available in red or black

SPECS	HiPRESS 2	HiPRESS 4	HiPRESS 4duo
volume of vessel	2 liters	4 liters	2 x 4 liters
filling capacity	1.5 liters	3 liters	6 liters (2 x 3 l)
propellant	compressed air	compressed air	compressed air
operation pressure	20 bar	20 bar	20 bar
duration	app. 10 sec.	app. 16 sec.	app. 30 sec.
jet range, last drop (normal/range nozzle)	app. 9 m/12m	app. 9 m/12m	app. 9 m/12m
range of temperature	* -25 to 60° C	* -25 to 60° C	* -25 to 60° C
weight (empty)	app. 2.6 kg	app. 3.5 kg	app. 7 kg
weight (filled)	app. 4.1 kg	app. 5.5 kg	app. 12 kg
height	425 mm	440 mm	440 mm
diameter of vessel(s)	110 mm	130 mm	130 mm
approval	SQ 62/15	SQ 15/15	SQ 59/15

* When using frost-proof extinguishing agent

optional accessories:



Jet gun holster:

Attached at the backpack's lap belt. A press of a button secures the jet gun

Refill kit for all 18-bar units:

Pressure reducer with gauge, connection tube, quick coupling, shut-off valve and compressed air cylinder 2 liter/300 bar (steel).



Portable refill case

Dust, shock and waterproof. For transporting the standard refilling equipment. With 8+8 bottles for water and additives, funnel and cleaning brush.

